

ELBOWS WITHOUT THE ELBOW GREASE

Introducing SpeedCouple pre-installed elbow coupling

Available on
rigid steel elbows

Standard &
special radius

Trade sizes 2-5

Listed as
concrete tight

For decades, contractors have had to rely on cumbersome three-piece couplings when installing elbows in tight spaces. Now with SpeedCouple, the process takes half the time. Just turn the coupling, not the elbow, and let the lead-in threads do most of the work. Boost productivity and cut material costs by up to 50% compared to three-piece couplings.

Watch the video at picoma.com/speedcouple





SpeedCouple: Pre-installed Coupling

Available on
rigid steel elbows
Standard & special radius
Trade sizes 2-5
Listed as concrete tight

SpeedCouple connects in half the time of conventional couplings. Just turn SpeedCouple, not the elbow, and let the lead-in threads do most of the work. It's easier on your crew and your budget!


WEIGHTS, DIMENSIONS AND PACKAGING FOR SPEEDCOUPLE ON 90° ELBOWS

TRADE SIZE	MIN. RADIUS	OFFSET	STRAIGHT	WEIGHT PER ELBOW	WEIGHT PER ELBOW WITH COUPLING	STANDARD CARTON QTY.
	in.	in.	in.	lbs.	lbs.	
2	9.5	14.54	5.04	6.70	7.58	5
2½	10.5	17.00	6.50	12.00	13.76	Bulk
3	13	19.67	6.67	19.00	20.98	Bulk
3½	15	22.72	7.72	28.00	30.65	Bulk
4	16	23.94	7.94	31.00	34.09	Bulk
5	24	34.90	10.90	68.00	71.97	Bulk

SpeedCouple with elbows shall be listed to safety standards UL-6 and UL-514B. Manufactured in accordance with ANSI® C80.1.
Standard-radius elbows: Available in 90°, 60°, 45°, 30°, 22½°, 15°, 11¼°
Special-radius elbows: Available in 90°, 60°, 45°, 30°, 22½°, 15°, 11¼°

Watch the video at picoma.com/speedcouple

PIC-092617

 9208 Jeffrey Drive
Cambridge, OH 43725
P 800.742.6621
F 740.439.4160

info@picoma.com
picoma.com

