

POWR-GARD® Technical Resource Littelfuse



Callas / Kingsley Electrical Sales
845 Lively Blvd.

Wood Dale, IL 60191

PH : 630-595-7887

Fax : 630-595-6922

email : info@ckelectricalsales.com

Local Stock @ Callas/Kingsley

CONDENSED CROSS REFERENCE GUIDE

This cross reference covers the most popular fuses for which there is a similar Littelfuse standard item. Furnished for your convenience, it is meant to serve as a guide for product selection. We suggest you check all applicable specifications before making substitutions. For special applications, more complete information, and for fuse block and medium voltage fuse cross referencing, visit Littelfuse.com or call 1-800-TEC-FUSE (1-800-832-3873).

Competitor	Littelfuse	Competitor	Littelfuse	Competitor	Littelfuse	Competitor	Littelfuse
10KOTN	NLN	CJ	JLS	JJN	JLLN	NON	NLN
10KOTS	NLS	CJS	JLS	JJS	JLLS	NOS	NLS
50KOTN	NLN	CLF	KLPC or KLLU	JKS	JLS	NRN	NLN
50KOTS	NLS	CLL	KLLU or KLPC	KA	115S	NRN (15-60A)	NLKP
A013F	L15S	CLU	KLLU or KLPC	KAB	L25S	NRS	NLS
A015F	L15S	CM	BLF	KAC	KLC	OT	NLN
A015R	L15S	CRN-R	FLNR ID'	KBH	L50S	OTM	BLF or BLN
A025F	L25S	CRS-R	FLSR ID	KLM	KLKD	OTN	NLN
A050F	L50S	CTN-R	KLNR	KLU	KLLU or KLPC	OTS	NLS
A060F	LOOS	CTS-R	KLSR	KN	KLNR	PV-(1-30)A10F	SPF
A070F	L70S	DCT	SPF'	KON	NLN	REN	RLN
A13X	L15S	EBS	BLS	KOS	NLS	RES	RLS
A25X	L25S	ECNR	FLNR ID'	KRP-C	KLPC	RF	RLN
A2D-R	LLNRK'	ECSR	FLSR ID	KS	KLSR	RFA	L15S
A2K-R	KLNR	ELN	LKN	KTK	KLK	RFC	KLC
A3T	JLLN	ELS	LKS	KTKR	KLKR	RFL (750V)	L70S (700 V)
A4BQ	KLPC	ERN	RLN	KTNR	KLNR	RFN (Mersen)	RLN
A4BT	KLLU or KLPC	ERS	RLS	KTSR	KLSR	RFS (Mersen)	RLS
A4BY	KLPC or KLLU	FNA	FLA	KTU	KLPC or LDC	RFV	L50S
A4J	JLS	FNM	FLM	LCL	KLPC or KLLU	REIN	KLNR
A50P (type 1 & 4)	L50S	FNQ	FLQ	LCU	KLPC or KLLU	RHS	KLSR
A6OX	LOOS	FNQ-R	KLDR	LENRK	LLNRK	RLN (Mersen)	LKN
A6D-R	LLSRK ID §	FRN-R	FLNR ID'	LESRK	LLSRK_ID	RLS (Mersen)	LKS
A6K-R	KLSR	FRS-R	FLSR ID	LKN	LKN	S	SOO
A6T	JLLS	FWA	L15S'	LKS	LKS	SA	SAO
A70P	L70S	FWH	L50S'	LKU	KLLU	SC	SLC
ABC	314	FWP	L70S *	LONRK	LLNRK	SEC	SLC
ACK	CCK	FWX	L25S *	LOSRK	LLSRK_ID	SF13X	L15S
AG	SLC	GDA	216	LPCC	CCMR	SF25X	L25S
AGA	AGA	GOB	217	LPJ(SP)	JTD_ID	SF50P	L50S
AGC	312	GDC	218	LPNRK (SP)	LLNRK	SF60X	L60S

Competitor	Littelfuse	Competitor	Littelfuse	Competitor	Littelfuse	Competitor	Littelfuse
AGU (1-30A)	BLN	GDL	313	LPSRK (SP)	LLSRK_ID'	SF7OP	L70S
AGW	AGW	GEB	LEB	MCL	KLK	SEE	SFE
AJT	JTD ID	GEBN	LET	MCR	251	SL	SLO
AMG	MEG	GFA	251	MDA	326	T	TOO
AMI	MID	GFN	FLA	MDL	313	TJN	JLLN
ANL	CNL	GGC	312	MDQ	313	TJS	JLLS
ANN	CNN E	GGM	235	MDV	315	TL	TLO
ASO	SPF	GLR	LGR	MDX	313	TR	FLNR_ID''
ATC	ATO (287)	GMA	235	MEN	FLM	TRM	FLM
AT-DE	FLNR ID'	GMD	239	MEQ	FLQ	TRN-R	FLNR_ID ^{2/} '
ATDR	CCMR	GMT	481	MID	FLA	TRS	FLSR_ID'
ATM (Mersen)	KLKD	HCLR	KLKR	MOF	BLN	TRS-R	FISR_ID ¹
ATMR	KLKR	HCTR	KLDR	MOL	BLF	XL25X	L25S
AM	FLQ	HEB	LEB	MTH	312	XL50F	L50S
AMR	KLDR	HET	LET	NCLR	KLNR	XL70F	L70S*
AX	481	HLR	LH R				
BAF	BLF	HP10M	SPF				
BAN	BLN	HP6J	SPFJ *				
BBS	BLS	JDL	JTD ID				
C519	229	JFL	JLS				
C520	225	JHC	JTD ID				

© 2013 Littelfuse POWR-GARD® Products

Littelfuse.com

A fuse may be used in circuits where the fuse's voltage rating is equal to or greater than the circuit voltage, unless otherwise stated on the fuse. For example, the FLSR ID indicating fuse has a voltage rating of 75-600 volts. This fuse can be used on 600 volts, 480 volts, 250 volts, 125 volts, or 75 volts. Never use a fuse in a circuit having a higher rated voltage than the fuse.

*** Check specific mounting dimensions before substituting.**

t Check characteristics and dimensions for application before substituting.

For Vio - 30 amperes, order non-indicating FLNR series fuses.

§ Verify voltage for DC applications.

Form: PF613

Rev: 1-A-091613